

Outside Diameter Information

AWWA C900 **(DR's 14, 18, 25)**

4 ----- 4.800
6 ----- 6.900
8 ----- 9.050
10 --- 11.100
12 --- 13.200

**First number
is nominal ID,
second number
is toleranced OD.**

ASTM D3034 **SDR's 35(PS46), SDR 26(PS115)**

4 ----- 4.215
6 ----- 6.275
8 ----- 8.400
10 --- 10.500
12 --- 12.500
15 --- 15.300

IP IRRIGATION PIPE

6 ----- 6.140
8 ----- 8.160
10 --- 10.200
12 --- 12.240
15 --- 15.300
18 --- 18.701
21 --- 22.047
24 --- 24.803
27 --- 27.953

ASTM D2241 **(SDR's 13.5, 17, 21, 26)**

2 ----- 2.375
2 1/2 - 2.875
3 ----- 3.500
3 1/2 - 4.000
4 ----- 4.500
6 ----- 6.625
8 ----- 8.625
10 --- 10.750
12 --- 12.750

AWWA C905 **(DR's 14, 18, 21, 25, 32.5, 41, 51)**

14 ----- 15.300
16 ----- 17.400
18 ----- 19.500
20 ----- 21.600
24 ----- 25.800
30 ----- 32.000
36 ----- 38.300
42 ----- 44.500
48 ----- 50.800

**Available from
FlexPVC.com**

ASTM F679 **SDR 35(PS46), SDR26(PS115)**

18 ----- 18.701
21 ----- 22.047
24 ----- 24.803
27 ----- 27.953
30 ----- 32.000
36 ----- 38.300
42 ----- 44.500
48 ----- 50.800