



300 S. DAYTON ST.  
 DAVISON, MI 48423  
 PH: 810-653-9626  
 FAX: 810-654-2616

Part Weight	0.15 lbs.
Min/Max Temp.	-30/140 Degrees F
Pressure Tested	4.3 PSI
Material	Flexible PVC 60 Duro Shore A
Installation Torque	
Conforms to ASTM	D5926
Box Quantity	
Clamps used	

**TOLERANCES:**  
 .X= Fractional ±  
 .XX= ±.060  
 .XXX= ±.032  
 ANG.= ±0.5°  
 UNLESS OTHERWISE SPECIFIED

UNITS: INCHES  
 SIZE: **A**  
 3RD ANGLE PROJECTION  
 DO NOT SCALE DRAWING

DESCRIPTION: Utility Connectors	
<b>UC-1575</b>	
DESIGNER: D. Brady	SCALE not to scale
CHECKER:	DATE: 3/1/2011
SHEET 1 OF 1	

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERRICO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERRICO, INC. IS PROHIBITED.